



**NOTES:**

1. WOVEN WIRE FENCE SHALL BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES. POSTS SHALL BE STEEL, EITHER 'T' OR 'U' TYPE OR HARDWOOD.
2. FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION. FENCE SHALL BE WOVEN WIRE, 6" MAXIMUM MESH OPENING.
3. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER, THEY SHALL BE OVERLAPPED BY SIX INCHES AND FOLDED. FILTER CLOTH SHALL BE EITHER FILTER X, MIRAFI 100X, STABLINKA T140N, OR APPROVED EQUIVALENT.
4. PREFABRICATED UNITS SHALL BE GEOFAB, ENVIROFENCE, OR APPROVED EQUIVALENT.
5. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED AND REPLACED WHEN "BULGES" DEVELOP IN THE SILT FENCE.
6. INSTALL FABRIC ON UPHILL SIDE OF SUPPORT POSTS.
7. SILT FENCE SHALL NOT BE USED IN DRAINAGE WAYS.

VILLAGE OF CROTON-ON-HUDSON  
STANDARD CONSTRUCTION DETAILS

**SILT FENCE**



VILLAGE OF CROTON-ON-HUDSON  
STANLEY H. KELLERHOUSE MUNICIPAL BUILDING  
1 VAN WYCK STREET (2ND FLOOR)  
WESTCHESTER COUNTY  
VILLAGE OF CROTON-ON-HUDSON, NY 10520  
PHONE: (914) 271-3775  
FAX: (914) 271-2856

PROJECT: DETAILS  
SCALE: NOT TO SCALE  
DATE: 04/10/2015

PREPARED IN THE  
OFFICE OF THE  
COMMISSIONER OF PUBLIC WORKS

DESIGNED BY: ARC, PE      CHECKED BY: ARC, PE  
DRAWN BY: ARC, PE      VOOOH SD-1A\_Silt Fence.dwg

SD-1A