



NOTES:

1. FILTER FABRIC SHALL HAVE AN AOS OF 40-85.
2. WOODEN FRAME SHALL BE CONSTRUCTED OF 2" X 4" CONSTRUCTION GRADE LUMBER.
3. WIRE MESH ACROSS THROAT SHALL BE A CONTINUOUS PIECE 30 INCH MINIMUM WIDTH WITH A LENGTH 4 FEET LONGER THAN THE THROAT. IT SHALL BE SHAPED AND SECURELY NAILED TO A 2" X 4" WEIR.
4. THE WEIR SHALL BE SECURELY NAILED TO 2" X 4" SPACERS 9 INCHES LONG SPACED NO MORE THAN 6 FEET APART.
5. THE ASSEMBLY SHALL BE PLACED AGAINST THE INLET AND SECURED BY 2" X 4" ANCHORS 2' LONG EXTENDING ACROSS THE TOP OF THE INLET AND HELD IN PLACE BY SANDBAGS OR ALTERNATE WIEGHTS.

MAXIMUM DRAINAGE AREA 1 ACRE

VILLAGE OF CROTON-ON-HUDSON
STANDARD CONSTRUCTION DETAILS

CURB INLET PROTECTION



VILLAGE OF CROTON-ON-HUDSON
STANLEY H. KELLERHOUSE MUNICIPAL BUILDING
1 VAN WYCK STREET (2ND FLOOR)
WESTCHESTER COUNTY
VILLAGE OF CROTON-ON-HUDSON, NY 10520
PHONE: (914) 271-3775
FAX: (914) 271-2856

PROJECT: DETAILS
SCALE: NOT TO SCALE
DATE: 04/10/2015

PREPARED IN THE
OFFICE OF THE
COMMISSIONER OF PUBLIC WORKS

DESIGNED BY: ARC, PE CHECKED BY: ARC, PE
DRAWN BY: ARC, PE VOGO SD-1D_Curb Inlet Protection.dwg

SD-1D